
LEE BROOM

ORION TUBE LIGHT (220-240V)





LED Driver Dimensions

Year of Design 2018

Dimensions

Suspension

 $10\text{cm} \times 6\text{cm} \times 3\text{cm}$ (3 % in \times 2 % in \times 1 % in) Suitable sized cavity / housing required for LED driver in ceiling or surface mounting.

Alternatively use deep canopy to mount LED driver in canopy.

PRODUCT DETAILS

V	la	n	1	e

Orion Tube Light

Finish & Product Code

Polished Gold • ORI0020
Polished Gunmetal • ORI0021

Materials

Opal acrylic tube, steel globe

Illumination


13.9W, 2700k, 1069 lumen, 24VDC, CRI 85 Supplied with separate LED driver with 220-240V input.

Dimming

Dimmable. Recommended dimmer for up to 8 units: Varilight V-Pro JPQ401 (120w) For more than 8 units, please contact us.

Certification

CE, CB



I \times Adjustable steel tensile wire & I \times Cord with transparent casing Kit to hang horizontally or vertically included.

Ceiling plate / Canopy

H 13cm x W 87.5cm

2 x mini canopies H 1.55cm x Dia 4cm, in matching finish to Orion.

Also available to order separately:

I x Side Entry Adapter for mini canopy, which enables LED driver to be surface mounted (increases height of mini canopy to 3.1cm). I x Deep Canopy that can mount LED driver in canopy if required (H $6.5 \, \mathrm{cm} \times \mathrm{Dia} \ \mathrm{I3cm}$).

 $\ensuremath{\mathsf{Ix}}$ Ceiling plate cover for junction box to mount mini canopy.

Weight

Product (net): 1.75 kg Boxed (gross): 2.66 kg



 ϵ


For more information please contact:

US & Canada Inquiries: +1 212 804 8477 - sales@leebroom.com

LEE BROOM

ORION TUBE LIGHT (IIO-I30V)





Must be installed with LED driver

LED driver to be installed remotely in suitable sized cavity / housing Refer to LED driver specification sheet for correct size of LED driver supplied with your particular Orion set-up.

PRODUCT DETAILS

V	la	m	ıe

Orion Tube Light

Finish & Product Code

Polished Gold • ORI0120
Polished Gunmetal • ORI0121

Materials

Opal acrylic tube, steel globe

Illumination

13.9W, 2700k, 1069 lumen, 24VDC, CRI 85 Supplied with separate LED driver with 110-130V input.

Dimming

Dimmable. Lutron C.L dimmers recommended for up to 8 units For more than 8 units, please contact us.

Certification

UL, cULus



Year of Design

2018

Dimensions

H 13cm x W 87.5cm - H 5 1/8 in x W 34 1/2 in

Suspension

Length: 500cm - 196 1/8 in

I \times Adjustable steel tensile wire & I \times Cord with transparent casing Kit to hang horizontally or vertically included.

Ceiling plate / Canopy

 $2 \times mini$ canopies in matching finish to Orion. H 1.55cm \times Dia 4cm - H $\frac{1}{2}$ in \times Dia 1 $\frac{1}{2}$ in

Also available to order separately:

I x Side Entry Adapter, which enables LED driver to be surface mounted (increases height of mini canopy to 3.1cm / 1½ in). I x Deep Canopy that can mount LED driver in canopy if required (H 6.5cm x Dia 13cm - H $2\frac{1}{2}$ in x Dia $5\frac{1}{6}$ in).

Ix Ceiling plate cover for junction box to mount mini canopy.

Weight

Product (net): 1.75 kg / 3.86 lbs Boxed (gross): 2.66 kg / 5.86 lbs



For more information please contact:

US & Canada Inquiries: +1 212 804 8477 - sales@leebroom.com